

# e951F 19" WIDE LED MONITOR



## PRODUCT SPECIFICATION

Display Size	19" Wide (481.3mm)
Native Resolution	1440 x 900
Response Time	5ms
Interfaces	Analog & DVI-D

## IMAGE QUALITY

Viewing Angle (horizontal)	170°
Viewing Angle (vertical)	160
Speaker	NA
Luminance	250 Cd/m <sup>2</sup>
Contrast Ratio	1000:1
Dynamic Contrast Ratio	20,000,000:1
Pixel Pitch	0.2835 mm
Colors Supported	16.7 Million
Frequency Range (Horizontal)	30 – 60KHz
Frequency Range (Vertical)	50 – 76Hz

## EASE OF USE FEATURES

On Screen Controls	Luminance, Image Setup, Color Setup, Picture Boost, OSD setup, Extra, Exit
Mac Compatibility	Yes
Stand	Tilt (-4° to 14°)

## ENVIRONMENT

Power	21W (Typ)
Operating Voltages	90-240 VAC; 50/60 Hz
Operating Temperature	0° to 45° C
Operating Relative Humidity	10 to 85 %

## REGULATORY COMPLIANCE

RoHS	Yes
Energy Star	Yes
Approvals and Certifications	FCC, CE, cCSAus, TUV-S, TUV-Bauart, ISO9241 - 307, EPEAT Silver, Windows7.

## DIMENSIONS AND WEIGHT

W x H x D (mm)	444.1 x 379.7 x 178.7
Package W x D x H (mm)	376 x 497 x 110
Net Weight	1.863 Kg
Gross weight	3.2Kg

## ADDITIONAL FEATURES

Ultra slim, Ultra High DCR, Multifunctional Stand, Direct insert, Touch key, e-saver, HDCP ready, Power saving mode, i-menu, Off timer, Low power consumption, Image ratio exchange, Screen+.



LED	16.7M Colors	Windows-7	Low Power	20 Million:1 DCR
Ultra Slim	DCB	MAGNETIC EXCHANGE	Eco Mode	Screen +
E-Saver	i-Menu	epeat SILVER	Off Timer	Direct Insert

# e2050S 20" WIDE LED MONITOR



## PRODUCT SPECIFICATION

Display Size	20" W (508 mm)
Native Resolution	1600 x 900
Response Time	5 ms
Interfaces	Analog (D-Sub)
Viewing Angle (horizontal)	170°
Viewing Angle (vertical)	160°
Speaker	NA

## IMAGE QUALITY

Luminance	200 Cd/m <sup>2</sup>
Contrast Ratio	1000:1
Dynamic Contrast Ratio	20,000,000:1
Pixel Pitch	0.2768 mm
Colors Supported	16.7 Million
Frequency Range (Horizontal)	30—83 KHz
Frequency Range (Vertical)	50—75 Hz

## EASE OF USE FEATURES

On Screen Controls	Luminance, Image Setup, Color Setup, Picture Boost, OSD setup, Extra, Exit
Mac Compatibility	Yes
Stand	Tilt (- 3° to 12°)
Wall Mounting	VESA 100 mm

## ENVIRONMENT

Power	18 W (Typ)
Operating Voltages	90-240 VAC;50/60 Hz
Operating Temperature	0° to 45°C
Operating Relative Humidity	10 to 85 %
RoHS	Yes

## REGULATORY COMPLIANCE

Energy Star	Yes
Approvals and Certifications	FCC, CE, cCSAus, TUV-S, ISO9241 - 307, EPEAT Silver, TCO 5.1, Windows7.
W x H x D (mm)	477.75 x 361 x 376

## DIMENSIONS AND WEIGHT
















Package W x D x H (mm)	528 x 108 x 376
Net Weight	3.4 Kg
Gross weight	4.7 Kg

## ADDITIONAL FEATURES

Super slim, Ultra High DCR, e-stand, Direct insert, Hair line texture, e-saver, i-menu, Piano polish, Off timer, Low power consumption, Shinning Edge & Clean ID with hidden key, Image ratio exchange, Screen+.

\* With a view to ensure ongoing product enhancement / development, we reserve the right to change any specifications, without prior notice.



 LED	 5ms	 Windows-7	 Low Power	 20 Million:1 DCR
 Ultra Slim	 Touch Key	 Resolution Exchange	 Eco Mode	 Screen +
 E-Saver	 VESA Mount	 epeat SILVER	 Off Timer	 Hg Free

# e2043Fsk 20" WIDE LED MONITOR



## PRODUCT SPECIFICATION

Display Size	20" W (508 mm)
Native Resolution	1600 x 900
Response Time	5 ms
Interfaces	Analog (D-Sub)
Viewing Angle (horizontal)	170°
Viewing Angle (vertical)	160°
Speaker	NA

## IMAGE QUALITY

Luminance	250 Cd/m <sup>2</sup>
Contrast Ratio	1000:1
Dynamic Contrast Ratio	50,000,000:1
Pixel Pitch	0.2766 mm
Colors Supported	16.7 Million
Frequency Range (Horizontal)	30—83 KHz
Frequency Range (Vertical)	55—75 Hz

## EASE OF USE FEATURES

On Screen Controls	ECO mode, Color Boost, Luminance, Image Setup, Color Temperature, Picture Boost, Extra, Exit
Mac Compatibility	Yes
Security	Kensington security lock slot
Stand	Tilt (-3° to 12°)
Wall Mounting	VESA 100 mm

## ENVIRONMENT

Power	18 W (Typ)
Operating Voltages	90-240 VAC; 50/60 Hz
Operating Temperature	0° to 45°C
Operating Relative Humidity	10 to 90 %
RoHS	Yes

## REGULATORY COMPLIANCE

Energy Star	Yes
Approvals and Certifications	cCSAus, FCC, CE, TUV-S, TUV-Bauart, EPEAT Silver, Windows7.
W x H x D (mm)	480.8 x 367.4 x 182
















## DIMENSIONS AND WEIGHT

Package W x D x H (mm)	539 x 499 x 124
Net Weight	2.3 Kg
Gross weight	5 Kg

## ADDITIONAL FEATURES

Ultra-Slim, Ultra High DCR, DCB, ECO mode, Off timer, Screen+, Illuminating touch key, e-Saver, Wall mount with Tilt functionality, Ultra Low power consumption, Glossy finish, and Image Ratio exchange.



- |   |   |  |   |  |
|---|---|--|---|--|
| <br><b>LED</b> | <br><b>5ms</b> | <br>Windows-7       | <br>Low Power | <br>50 Million:1<br>DCR |
| <br>Ultra Slim | <br>Touch Key  | <br>Metallic Finish | <br>Eco Mode  | <br>Screen +            |
| <br>E-Saver    | <br>VESA Mount | <br>epeat<br>SILVER | <br>Off Timer | <br>Hg Free             |

# e2243Fw2k 21.5" WIDE LED MONITOR



## PRODUCT SPECIFICATION

Display Size	21.5"W (547mm)
Native Resolution	1920 x 1080
Response Time	2 ms (GTG)
Interfaces	Analog RGB and HDMI x 2
Viewing Angle (horizontal)	170°
Viewing Angle (vertical)	160°
Speaker	NA

## IMAGE QUALITY

Luminance	250 Cd/m2
Contrast Ratio	1000:1
Dynamic Contrast Ratio	50,000,000:1
Pixel Pitch	0.248 mm
Colors Supported	16.7 Million
Frequency Range (Horizontal)	30—83 KHz
Frequency Range (Vertical)	55—75 Hz

## EASE OF USE FEATURES

On Screen Controls	ECO mode, Color Boost, Luminance, Image Setup, Color Temperature, Picture Boost, Extra, Exit
Mac Compatibility	Yes
Security	Kensington security lock slot
Stand	Tilt (- 3° to 12°)
Wall Mounting	VESA 100 mm

## ENVIRONMENT

Power	20 W (Typ)
DC input	12VDC, 3A
Operating Temperature	0° to 45° C
Operating Relative Humidity	10 to 90 %

## REGULATORY COMPLIANCE

RoHS	Yes
Energy Star	Yes
Approvals and Certifications	cCSAus, FCC, CE, RoHS and Windows7.

## DIMENSIONS AND WEIGHT

W x H x D (mm)	514.24 x 386.13 x 182
Package W x D x H (mm)	568 x 518 x 117
Net Weight	2.53Kg
Gross weight	4.98 Kg


## ADDITIONAL FEATURES

Ultra-Slim, Ultra High DCR, DCB, ECO mode, Off timer, Screen+, Illuminating touch key, e-Saver, Wall mount with Tilt functionality, Ultra Low power consumption, Glossy finish, and Image Ratio exchange.



# AOC

# e2260Swn



## DISPLAY SPECIFICATION

Display Size	: 21.5" Wide ( 546.86 mm diagonal)
Native Resolution	: 1920 x 1080
Response Time	: 5 ms
Viewing Angle	: 90° (H) / 50° (V)
Luminance	: 200 Cd/m2
Contrast Ratio	: 600:1
Dynamic Contrast Ratio	: 20,000,000:1
Pixel Pitch	: 0.248 mm
Colors Supported	: 16.7 Million
Frequency Range	: 30-83 KHz (H) / 56-76Hz (V)



## CONNECTIVITY

Analog Input	: VGA connector
--------------	-----------------

## POWER

Power Consumption	: 25W (Typical)
Stand-by Power	: ≤ 0.5W
Power supply	: 100-240 VAC; 50/60 Hz



## COMPLIANCE

Approvals/Environmental	: CE,cTUVus,FCC,Energy Star,RoHS,Windows 7,EPEAT Gold
Wall mount (mm)	: VESA 100 x 100



## DIMENSIONS AND WEIGHT

W x H x D (mm)	: 511 x 373 x 185
Net Weight	: 2.67Kg
Gross weight	: 3.86Kg



# AOC

# e2250Sw





## DISPLAY SPECIFICATION

Display Size	: 21.5" W (547 mm diagonal)
Native Resolution	: 1920 x 1080
Response Time	: 5 ms
Viewing Angle	: 170° (Horizontal) / 160° (Vertical)
Luminance	: 250 Cd/m2
Dynamic Contrast Ratio	: 20,000,000:1
Pixel Pitch	: 0.248 mm
Colors Supported	: 16.7 Million
Frequency Range	: 30-83 KHz (Horizontal) / 55-75Hz (Vertical)



## DISPLAY INTERFACES

Analog Input	: 15-pin D-sub connector
--------------	--------------------------



## POWER AND OTHERS

Power Consumption	: 23W (Typical)
Stand-by Power	: ≤0.5W
Power Supply	: 90-240 VAC; 50/60 Hz
Stand Tilt	: -4° to 17°
Approvals and Certifications	: FCC, CE, cCSAus, Energy star, RoHS, EPEAT Silver, Windows7.



## DIMENSIONS AND WEIGHT

Wall mount (mm)	: 75 x 75
W x H x D (mm)	: 511.18 × 379.95 × 190
Net Weight	: 3.28Kg
Gross weight	: 4.06Kg





- LED
- 2x HDMI™
- Windows-7
- Low Power
- 50000000 :1 DCR
- Ultra Slim
- Touch Key
- 2ms
- ENERGY STAR
- Screen +
- VESA Mount
- epeat SILVER
- Off Timer

# e2343F2k

## 23" WIDE LED MONITOR



### PRODUCT SPECIFICATION

Display Size	23" W (584.2 mm)
Native Resolution	1920 x 1080
Response Time	5 ms
Interfaces	Analog and DVI-D
Viewing Angle (horizontal)	170°
Viewing Angle (vertical)	160°
Speaker	NA

### IMAGE QUALITY

Luminance	250 Cd/m2
Contrast Ratio	1000:1
Dynamic Contrast Ratio	50,000,000:1
Pixel Pitch	0.265 mm
Colors Supported	16.7 Million
Frequency Range (Horizontal)	30—83 KHz
Frequency Range (Vertical)	55—75 Hz

### EASE OF USE FEATURES

On Screen Controls	ECO mode, Color Boost, Luminance, Image Setup, Color Temperature, Picture Boost, Extra, Exit
Mac Compatibility	Yes
Security	lockslot security Kensington
Stand	Tilt (- 3°to 12°)
Wall Mounting	VESA 100 mm

### ENVIRONMENT

Power	28 W (Typ)
Operating Voltages	90-240 VAC;50/60 Hz
Operating Temperature	0°to 45°C
Operating Relative Humidity	10 to 90 %
RoHS	Yes

### REGULATORY COMPLIANCE

Energy Star	Yes
Approvals and Certifications	cCSAus, FCC, CE, TUV-S, TUV-Bauart, EPEAT Silver, Windows7.
W x H x D (mm)	547.2 × 404.6 × 182.4

### DIMENSIONS AND WEIGHT

Package W x D x H (mm)	608 × 117 × 538
Net Weight	2.5 Kg
Gross weight	5.4 Kg

### ADDITIONAL FEATURES

Ultra-Slim, Ultra High DCR, DCB, ECO mode, Off timer, Screen+, Illuminating touch key, e-Saver, Wall mount with Tilt functionality, Ultra Low power consumption, Glossy finish, and Image Ratio exchange.

# AOC

# e2462Vwh



# Product Specification

## DISPLAY SPECIFICATION

Display Size	: 23.6" Wide (598 mm diagonal)
Native Resolution	: 1920 x 1080
Response Time	: 2 ms (GTG)
Viewing Angle	: 170° (H) / 160° (V)
Luminance	: 250 Cd/m <sup>2</sup>
Contrast Ratio	: 1000:1
Dynamic Contrast Ratio	: 20,000,000:1
Pixel Pitch	: 0.248 mm
Colors Supported	: 16.7 Million
Frequency Range	: 30-83 KHz (H) / 50-76 Hz (V)



## CONNECTIVITY

Analog Input	: VGA connector
Digital Input	: HDMI connector
Audio out	: Earphone Jack (only with HDMI in)

## POWER

Power Consumption	: 24 W (Typical)
Stand-by Power	: ≤ 0.5W
Power supply	: 12V DC,3A External adapter



## COMPLIANCE

Approvals/Environmental	: FCC,CE/CB, cTUVus,TUV-S,TUV-Bauart, Windows 7, ISO9241-307,EPA,RoHS,BSMI,TCO 5
-------------------------	--



## DIMENSIONS AND WEIGHT

W x H x D (mm)	: 567.38 x 417.55 x 208.85
Net Weight	: 3.75 Kg
Gross weight	: 5.4 Kg

